



P^π1

OzoSense Selection Guide

		OzoSense M	OzoSense NM
			
	Spare Sensor Pt. No.	32000010	35003101
	Sensor Bundle Pt. No.	38000090	35003102
Applications	Process	✓	✓
	Potable Water	✓	✓
	Seawater	✓	✗
Mounting Options	Single Open Flow Cell	✓	✗
	Dual Open Flow Cell	✓	✗
	Triple Open Flow Cell	✓	✗
	Closed Flow Cell	✓ (not recommended)	✓
	Autoclean (Flow Cell)	✓	✗
Specifications	Standard Cable Length	5m	2m
	Inbuilt Temperature	✓	✓
	Max. Temperature	45°C	70°C
	Automatic Temp. Compensation	✓	✓
	Max. Pressure	1 Bar	6 Bar
	Response Time (T ₉₀)	50 secs	<2 secs
	pH Range	2 to 11	4 to 10
	Insensitive to Chlorine	✓	✗
	Electrolyte Required	✓	✗

Mounting Options



Single Open Flow Cell (OzoSense M)
PN:32100001



Double Open Flow Cell (OzoSense M
and e.g. chlorite)
PN:32100002



Triple Open Flow Cell (OzoSense M
and e.g. chlorite and pH)
PN:32100007



Single Closed Flow Cell (OzoSense M)
PN:32100010



Single Closed Flow Cell (OzoSense NM)
PN: 35003103

Autoclean Options



Autoflush Cell (OzoSense M)
PN:36500001

Options



Flow Regulator (OzoSense NM)
PN:37001304